



CERAMIC COLLECTION®

Gann tile

cerámico artesanal de la colección Ceramic, fabricado con material Impact®. Formato 40 × 10 cm, disponible en acabado Mate, Esmaltado Brillo y Cemento. Apto para revestir paredes y fachadas en interior y exterior. tile

01 Data sheet

TECHNICAL DATA



Format	40 × 10 cm
Thickness	2,4 cm
Material	Impact®
Finish	Mate · Esmaltado Brillo · Cemento
Styles	Exacto tile
Application	Wall and façade · Interior and exterior

Ceramic **GANN 40x10**

Medidas en cm. / Measures in cm.

AZULEJO EXACTO · PIEZA IZQUIERDA Y DERECHA

Las medidas de fabricación son exactas.



Las medidas pueden variar +/- hasta 5 mm.

Dimensions in cm.

02 Colour range

FINISH COLOURS

MATE



Blanco

Ref. M1

Crema

Ref. M2

Arena

Ref. M4

Gris Claro

Ref. M3

Gris Oscuro

Ref. M7

Chocolate

Ref. M24

Terracota Oscuro

Ref. M18



Cuero

Ref. M19

Granate

Ref. M20

Salvia

Ref. M21

Musgo

Ref. M22

Petróleo

Ref. M23

ESMALTADO BRILLO



Blanco

Ref. B1

Crema

Ref. B2

Arena

Ref. B4

Gris Claro

Ref. B3

Gris Oscuro

Ref. B7

Chocolate

Ref. B24

Terracota Oscuro

Ref. B18



Cuero

Ref. B19

Granate

Ref. B20

Salvia

Ref. B21

Musgo

Ref. B22

Petróleo

Ref. B23

CEMENTO



Cemento Blanco

Ref. C1

Cemento Gris

Ref. C25

Cemento Antracita

Ref. C26

Every model is available in the **three finishes** with the same colour chart. The reference is shown next to each colour.

Custom colour option (RAL) in Mate or Brillo on request.

03 Specifications

FEATURES

 Fire-resistant

 Thermal insulation

 Acoustic insulation

 Waterproof

 Lightweight

 Interior

 Exterior

IMPACT

INTERIOR AND EXTERIOR

A material made with a base and mortars —a mix of technical cements, silicas, calcium carbonate, micas and lightening and fire-retardant additives— that make Impact® an extra high-quality material. It stands out for its strength, adhesion and impermeability, and for standing up to the outdoors, to fire and to all kinds of weather, with high resistance to abrasion and chemicals. Its light weight and minimal thickness make fitting very straightforward. Suitable for interiors and exteriors.

Impact®

technology

MATERIAL

B-s1,d0

Euroclass

REACTION TO FIRE

Thermal

+ acoustic

INSULATION

Int/Ext

APPLICATION

04 Installation

INSTALLATION


Fitting the Gann tile is quick and straightforward: **in just 3 steps, with no building work**. Apply bonding filler to the back of the piece and press it against the wall or façade, indoors or out.



1

Pick up the tile

Choose the piece and get it ready to fit.



2

Apply the adhesive compound

Apply the compound to the back.



3

Fit it to the wall or façade

Press each piece onto the surface.

FITTING ACCESSORIES		
MSA-3 · Bonding filler		1 cartridge / several tiles
MSA-70 · Joint filler (optional)		to grout between pieces
No building work		no chasing or bricklaying required