



CERAMIC COLLECTION®

Onix tile

Handmade ceramic tile from the Ceramic collection, made with Impact® material. Format 40 × 10 cm · 3 pieces (Onix-1, 2 and 3), available in Mate, Esmaltado Brillo and Cemento finishes. Suitable for cladding walls and façades, indoors and outdoors.

01 Data sheet

TECHNICAL DATA


Format	40 × 10 cm · 3 pieces (Onix-1, 2 and 3)
Thickness	1,4 – 2,8 cm
Material	Impact®
Finish	Mate · Esmaltado Brillo · Cemento
Styles	Exacto tile
Application	Wall and façade · Interior and exterior

Ceramic ONIX 40x10

Medidas en cm. / Measures in cm.

AZULEJO EXACTO

Las medidas de fabricación son exactas.



Dimensions in cm.

02 Colour range

FINISH COLOURS

MATE



Blanco
Ref. M1



Crema
Ref. M2



Arena
Ref. M4



Gris Claro
Ref. M3



Gris Oscuro
Ref. M7



Chocolate
Ref. M24



Terracota Oscuro
Ref. M18



Cuero
Ref. M19



Granate
Ref. M20



Salvia
Ref. M21



Musgo
Ref. M22



Petróleo
Ref. M23

ESMALTADO BRILLO



Blanco
Ref. B1



Crema
Ref. B2



Arena
Ref. B4



Gris Claro
Ref. B3



Gris Oscuro
Ref. B7



Chocolate
Ref. B24



Terracota Oscuro
Ref. B18



Cuero
Ref. B19



Granate
Ref. B20



Salvia
Ref. B21



Musgo
Ref. B22




Petróleo
Ref. B23


CEMENTO



Cemento Blanco
Ref. C1



Cemento Gris
Ref. C25



Cemento Antracita
Ref. C26

Every model is available in the **three finishes** with the same colour chart. The reference is shown next to each colour.

Custom colour option (RAL) in Mate or Brillo on request.

03 Specifications

FEATURES

 Fire-resistant

 Thermal insulation

 Acoustic insulation

 Waterproof

 Lightweight

 Interior

 Exterior

IMPACT

INTERIOR AND EXTERIOR

A material made with a base and mortars —a mix of technical cements, silicas, calcium carbonate, micas and lightening and fire-retardant additives— that make Impact® an extra high-quality material. It stands out for its strength, adhesion and impermeability, and for standing up to the outdoors, to fire and to all kinds of weather, with high resistance to abrasion and chemicals. Its light weight and minimal thickness make fitting very straightforward. Suitable for interiors and exteriors.

Impact®

technology

MATERIAL

B-s1,d0

Euroclass

REACTION TO FIRE

Thermal

+ acoustic

INSULATION

Int/Ext

APPLICATION

04 Installation

INSTALLATION


Fitting the Onix tile is quick and straightforward: **in just 3 steps, with no building work**. Apply bonding filler to the back of the piece and press it against the wall or façade, indoors or out.



1

Pick up the tile

Choose the piece and get it ready to fit.



2

Apply the adhesive compound

Apply the compound to the back.



3

Fit it to the wall or façade

Press each piece onto the surface.

FITTING ACCESSORIES		
MSA-3 · Bonding filler		1 cartridge / several tiles
MSA-70 · Joint filler (optional)		to grout between pieces
No building work		no chasing or bricklaying required